Frequency converter, motor leads and Vacuum cleaning

Frequency converters



SKC 750 frequency converter, suitable for iSA 500, iSA 750 + iSA 900 Part no.: 311707 6000

SKC 1500 frequency converter, suitable for iSA 1500 + iSA 2200 Part no.: 311715 6000

SKC 4000 frequency converter, suitable for iSA 3600 Part no.: 311740 6500

Length measurement sensor and motor leads

- Compact, pulse width modulated equipment in three output classes
- Input voltage, 230 V AC, single phase (SKC 750/1500) or 400 V AC, three phase (SKC 4000)
- Three phase, vector controlled control voltage frequency 0...1500 Hz
- Fast spindle braking with highly stressed, integrated brake resistance in the sub-frame
- Turn-off EMC filter
- Programmable inputs and outputs, relay output
- User-friendly control unit for configuring spindles
- 95 operating and display parameters for both simple and demanding applications (e. g. spindle energy sink in no load)
- Protection class: IP 20
- Control types: SPS; 0...10 V; 0...20 mA; with operating unit; CAN Bus (additional module required)
- Approved: CE; C-Tick; UL



Length measuring sensor for measuring tool lengths Part no.: 239099 0001

- 8-wire $(3x \ 0.75 \ \text{mm}^2 + 1x \ \text{PE} + 2x(2 \times 0.34 \ \text{mm}^2))$
- Drag chain compatible
- External braiding and separately shielded pairs
- Pre-fabricated

Motor side - M23 plug Converter side - wire end bushings Part no.: 392306 0300 (3 m) Part no.: 392306 0500 (5 m) Part no.: 392306 0800 (8 m)

Motor side - direct connection

Converter side - wire end bushings Part no.: 392301 0300 (3 m) Part no.: 392301 0500 (5 m) Part no.: 392301 0800 (8 m)

Vacuum cleaning

| for iSA 500 + iSA 750 spindles • prepared for hose 38 mm • manual opening | Part no.: 239012 0000 | Dust cover closed | Air hose inside |
|--|-----------------------|----------------------|--|
| for iSA 900 spindle prepared for hose 50 mm automatic opening | Part no.: 239012 0004 | | diameter 80 mm |
| for iSA 1500 spindle prepared for hose 80 mm manual opening | Part no.: 239012 0001 | | |
| for iSA 2200 spindle prepared for hose 80 mm automatic opening | Part no.: 239012 0002 | | |
| for iSA 2200 spindle with external CoolMin prepared for hose 80 mm automatic opening | Part no.: 239012 0003 | 8 8 | |
| for iSA 3600 spindle prepared for hose 80 mm | Part no.: 239012 0005 | | - C |
| pneumatic opening | | Dust cover open | A second se |
| Technical specifications subject to change. | | | |